



POWER METER

AR-PM

PACKAGE

Power Meter *1
 User Manual *1
 1.5V AA Batteries *3
 Soft Carrying Case *1
 Cotton Swabs

FEATURES

- Comfortable LCD display and optional backlight LCD display supports night operation.
- Power measurements in dBm or mw and insertion loss in dB.
- Reference power level storage(Ref Setting).
- Low battery consumption, more than 240 hours continual operation time with three 1.5V alkaline batteries.
- 10 minutes Auto-off function can be activated or deactivated.

APPLICATIONS

- Maintenance in Telecom.
- Maintenance in CATV.
- Fiber Optic Lab Testing.
- Other Fiber Optic Measurements.

SPECIFICATIONS

Wavelength(nm)	800~1700nm
Detector	InGaAs
Measurement Range (dBm)	-70~+3/-50~+26
Uncertainty	±5%
Calibrated Wavelength(nm)	850,1300, 1310,1490, 1550, 1610,1625
Resolution(dB)	0.01
Optical Connector	FC (interchangeable SC,ST) / as well as 2.5mm universal
Power Supply	Alkaline Battery(3 AA 1.5V batteries)
Battery Operating Time	240 h with 1.5V Battery(3)
Operating Temperature(°C)	-10 ~ +60
Storage Temperature(°C)	-25 ~ +70
Relative Humidity	0 to 95% (non-condensing)
Dimension(mm)	200 X90 X50
Weight(g)	285